

Jagoteq **LF40 Controller**

Jago Controller for Side Emitting Fiber Optic

Superior Technology

- Combining multiple lasers into one light source with an infinite amount of light color options
- Emits light at 360 degrees
- Direct replacement of LED technology with brighter and more saturated color light output

Efficient and Cost Effective

- No change in work methods required for lighting professionals
- Simple installation process that reduces labor hours and material costs
- Requires no additional hardware

Environmentally Friendly

- Can be reused indefinitely with care
- Aligns with studios goals for ESG initiatives
- Fiber optic cable can be recycled

Controller Features:

Data Control: 5 pin DMX control
Ethernet: Allows for control via Artnet/sACN
Wireless DMX
Bluetooth
Power: 120V-12V DC Barrel Connector
Internal Compartment for Battery or AC
Firmware updates: USB-A port
Fiber Connection: SMA-905
Fiber Optic cable Outputs: 1
Power consumption: 2 A
UI: 2x3.1" color screen
Managed by Rotary Knob
Screens are dimmable
Cooling: Heat sink/Smart Fan Control
Ambient operating temperature: 34F-98F
Noise Level: 45dB at full operating power allow
for use on film/TV sets
Quiet and Super Quiet Modes for limited time

Weight: 3lbs
Dimensions: 7.5"W x 4"H x 7"D
Material: High Impact Plastic
Vinyl Wrap
Rigging points: 1/4" 20
female inserts
"D" rings

Fiber Compatibility: 1mm, 3mm
and 6mm

Handling: Must be
handled with care
and kept free of

Safety: IR detection of fiber and mechanical safety components.
Safety Certifications: ETL, CA, 3R, CE in UKCA (in process)
ROHS compliant



Sales/Rental: Craig Brink 310-740-1255 Craig@jagoteq.com